

RECEIVED  
CENTRAL FAX CENTER

JAN 30 2006

To: Facsimile Number: 571-273-8300

Total Pages Sent 12

From:

Texas Instruments Incorporated  
Facsimile: 972-917-4418

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of

Applicant: Edwin Park

Docket Number: TI-31696

Serial No.: 09/975,364

Art Unit: 2182

Filed: 10/11/01

Examiner: Justin R. Knapp

For: Universal Interface Simulating Multiple Interface Protocols

CERTIFICATION OF FACSIMILE TRANSMISSION

I hereby certify that the following papers are being transmitted by facsimile to the U.S. Patent and Trademark Office on the date shown below:

Karen Vertz  
Karen Vertz

1-30-06  
Date

FACSIMILE COVER SHEET

<input checked="" type="checkbox"/> FACSIMILE COVER SHEET	<input type="checkbox"/> AMENDMENT (# pages)
<input type="checkbox"/> NEW APPLICATION	<input type="checkbox"/> EOT
<input type="checkbox"/> DECLARATION	<input type="checkbox"/> NOTICE OF APPEAL
<input type="checkbox"/> ASSIGNMENT	<input checked="" type="checkbox"/> APPEAL BRIEF (11 Pages)
<input type="checkbox"/> FORMAL DRAWINGS	<input type="checkbox"/> ISSUE FEE & PUBLICATION FEE (1 Page)
<input type="checkbox"/> INFORMAL DRAWINGS	<input type="checkbox"/> REPLY BRIEF (IN TRIPLICATE) (# Pages)
<input type="checkbox"/> CONTINUATION APP'N	
<input type="checkbox"/> DIVISIONAL APP'N	
NAME OF INVENTOR(S): Edwin Park	
TITLE OF INVENTION: Universal Interface Simulating Multiple Interface Protocols	
TI FILE NO.: TI-31696	DEPOSIT ACCT. NO.: 20-0668
FAXED: 1-30-06 DUE: 1-31-06 ATTY/SECY: AKS/kjv	
RECEIPT DATE & SERIAL NO.: Serial No.: 09/975,364 Filing Date: 10/11/01	

This facsimile is intended only for the use of the address named and contains legally privileged and/or confidential information. If you are not the intended recipient of this telecopy, you are hereby notified that any dissemination, distribution, copying or use of this communication is strictly prohibited. Applicable privileges are not waived by virtue of the document having been transmitted by Facsimile. Any misdirected facsimiles should be returned to the sender by mail at the address indicated on this cover sheet.

Texas Instruments Incorporated  
PO Box 655474, M/S 3999  
Dallas, TX 75265-5474

RECEIVED  
CENTRAL FAX CENTER  
JAN 30 2006

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Edwin Park

Art Unit: 2182

Serial No.: 09/975,364

Examiner: Justin R. Knapp

Filed: 10/11/01

Docket: TI-31696

For: UNIVERSAL INTERFACE SIMULATING MULTIPLE INTERFACE PROTOCOLS

APPELLANTS' BRIEF UNDER 37 C.F.R. §1.192

Commissioner of Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

CERTIFICATION OF FACSIMILE TRANSMISSION	
I hereby certify that the above correspondence is being transmitted by facsimile to the U.S. Patent and Trademark Office at 571-273-8300 on the date shown below:	
<u>Karen Vertz</u> Karen Vertz	<u>1-30-06</u> Date

Dear Commissioner:

The following Appeal Brief is respectfully submitted in connection with the above-identified application in response to the Final Rejection mailed August 30, 2005. Please charge all required fees, including any extension of time fees, to the deposit account of Texas Instruments Incorporated, Deposit Account No. 20-0668.

TI-31696 Page 1

JAN 30 2006

**REAL PARTY IN INTEREST**

The real party in interest is Texas Instruments Incorporated, to whom this application is assigned.

**RELATED APPEALS AND INTERFERENCES**

There are no related appeals or interferences known to the Applicant's legal representative.

**STATUS OF THE CLAIMS**

Claims 1, 2, 4-6, 8 and 9 are the subject of this appeal. Claims 1, 2, 4-6, 8 and 9 are rejected. Claims 3, 7 and 10-23 have been cancelled. This application was filed on October 11, 2001.

**STATUS OF THE AMENDMENTS**

The Appellants filed an amendment under 37 C.F.R. § 1.111 on June 20, 2005 in response to the Office Action dated March 21, 2005. The Appellants filed an amendment under 37 C.F.R. § 1.116 on September 26, 2005 in response to the Office Action dated August 30, 2005.

JAN 30 2006

### **SUMMARY OF CLAIMED SUBJECT MATTER**

Specification page 7, line 1 to page 9, line 2, provides a concise explanation of the invention defined in independent claim 1. In the preferred embodiment, the universal interface apparatus is able to support a number of 2-4 wire (line) devices using a software programmable block in which the control and data waveforms needed to support the protocols are all run time programmable. The UIA is able to support as illustrative example, protocols such as I2S, SSP, I2C, SPI, SBI, synthesizer programming, etc. Also, for SSP/PCM the UIA will not only support basic modes line 8 kHz voice, but will also support a variety of data sync waveforms, slots and data rates. The UIA will also allow the pads (interface pins) to change mode from one protocol to another at set up or run time to support the various needs of the application and customers. Optionally, multiplexers can also be used in order to allow the UIA to support multiple peripheral devices in a time multiplexed environment using the same interconnection pads.

FIGURE 1A shows an illustrative hardware environment, including telephone circuitry 150 wherein the universal interface apparatus 100 is located. The universal interface apparatus enables communications between a central processing unit (CPU) or digital signal processor (DSP) 152 (or other control hardware/software) and

peripheral devices 156, 160. The apparatus 100 includes processing circuitry that may be co-located, integrated, or even one-and-the-same with the CPU 152. In this example, the apparatus 100 has a number of input/output (I/O) lines 155. Some of the lines are coupled to a jack 158, enabling connection of the apparatus 100 to an "off-board" peripheral device 160 located apart from the telephone circuitry 150. The device 160 may comprise a component such as a multimedia card (MMC), etc. Other of the lines 155 are coupled to an "on-board" peripheral device 156 that is located on the telephone circuit 150, and accordingly hard-wired to the apparatus 100. The device 156 may comprise a component such as a radio front-end IC. The apparatus 100 includes still other lines 162, for connection to other peripheral device(s) (not shown).

The universal interface apparatus of this invention may be embodied by various hardware components and interconnections, one example of which is shown by the apparatus 100 of FIGURE 1B. The components of the universal serial interface apparatus 100 include a controller 104, memory 114, storage 120, clock 110 and optional multiplexer 112 ("mux"). If desired, the foregoing components may be provided together on the same circuit structure 102, such as an application-specific integrated circuit (ASIC). In this embodiment, the circuit 102 includes multiple pads 118 such as pins, connectors, ASIC pads, terminals, or other means to couple signal paths between the circuit 102 and off-circuit devices to which the apparatus 100 is providing an interface.

In one embodiment, the apparatus provides an interface between a main processor (not shown, e.g., CPU 152) and the off-circuit, "peripheral" device. For communications with the main processor, the controller 104 includes numerous I/O

lines 130. The controller 104 communicates with the peripheral device via the memory 114,, pads 118, and optionally the converter 122 and mux 112 . In another embodiment, the controller 104 and main processor may be co-located or even provided by the same device. For instance, the controller 104 may perform one application program involving main processor duties, and another, concurrent application program involving operation of the interface 100.

The controller 104 serves to selectively reconfigure components such as the clock 110, and memory 114, to interface a general purpose processor with an off-circuit, communications device attached to the pads 118. Additionally, by utilizing techniques such as time multiplexing using mux 112, the controller 104 may further direct the apparatus 100 to concurrently interface with multiple off-circuit devices coupled to the pads.

#### **GROUND OF REJECTION TO BE REVIEWED ON APPEAL**

Claims 1, 2, 4-6, 8, and 9 stand rejected under 35 U.S.C. § 102 (a) as being anticipated by U.S. Patent No. 6,189,052.

## **ARGUMENT**

Rejection under 35 U.S.C. § 102 (a) over U.S. Patent No. 6,189,052 .

Claims 1, 2, 4-6, 8, and 9


Claim 1 includes "... a multiplexer coupled between the memory and the plurality of interconnection pads wherein the universal interface device concurrently interfaces with the plurality of different peripheral devices using time multiplexing of the plurality of interconnection pads." The references of record do not show, teach, or suggest the above recited limitation of claim 1. U.S. Patent No. 6,189,052 does not disclose a multiplexer for time multiplexing coupled between the memory and the plurality of interconnection pads wherein the universal interface device concurrently interfaces with the plurality of different peripheral devices. U.S. Patent No. 6,189,052 does not have a time multiplexer coupled between the memory and the interconnection pads.

## CONCLUSION

For the foregoing reasons, Appellants respectfully submit that the Examiner's final rejection of Claims 1, 2, 4-6, 8 and 9 is improper, and it is respectfully requested that the Board of Patent Appeals and Interferences so find and reverse the Examiner's rejection.

Please charge any fees necessary in connection with the filing of this paper, including any necessary extension of time fees, to Deposit Account No. 20-0668 of Texas Instruments Incorporated.

Respectfully submitted,



Alan K. Stewart  
Attorney for Appellant  
Registration No. 35,373

Texas Instruments, Incorporated  
P. O. Box 655474 - M/S 3999  
Patent Department  
Dallas, Texas 75265  
972/917-5466



## CLAIMS APPENDIX

1. A universal interface device, comprising:
  - a controller;
  - a configuration database coupled to the controller, said configuration database having stored therein a plurality of different configuration protocols for supporting a plurality of different peripheral devices;
  - a plurality of interconnection pads;
  - a memory coupled to the interconnection pads and controller, the memory is programmable by the controller in order to support any of the different peripheral devices; and
  - a multiplexer coupled between the memory and the plurality of interconnection pads wherein the universal interface device concurrently interfaces with the plurality of different peripheral devices using time multiplexing of the plurality of interconnection pads.
2. A universal interface device as defined in claim 1, wherein the controller comprises a state machine.
4. A universal interface device as defined in claim 1, further comprising a programmable clock coupled to the memory or the configuration database.

5. A universal interface device as defined in claim 1, wherein the controller selects a configuration protocol from amongst the plurality of configuration protocols in the configuration database, and uses the selected configuration protocol to configure the memory in order to support the peripheral device from amongst the plurality that is coupled to the plurality of interconnection pads.
6. A universal interface device as defined in claim 2, wherein the state machine includes a programmable routing and mapping scheme that allows the state machine to communicate with more than one peripheral device that is coupled to the plurality of interconnection pads.
8. A universal interface as defined in claim 2, wherein the memory can be divided up by the state machine into two or more parts in order to support a peripheral device coupled to the interconnection pads that requires continuous transfer of data, the state machine switching between the two or more parts of the memory during data transfer to the peripheral device.
9. A universal interface as defined in claim 2, wherein the state machine sets a portion of the memory to provide a tri-state control if one or more of the plurality of interconnection pads have to function as both an input and an output.

## **EVIDENCE APPENDIX**

None.

**RELATED PROCEEDINGS APPENDIX**

None.